

MAGMA FIRESTOP **TG-3**

INNOVATIVE FIRE RETARDANT SOLUTIONS

Magma Firestop TG-3 is a fire retardant impregnation liquid for interior and exterior usage. This water-based, polymer formulation has leach resistant properties and gives a neutral effect to the timber. Magma Firestop TG-3 can be easily applied by immersion, spraying, rolling or by industrial coating method and gives a clear, colorless finish.



- Environmental friendly product
- Economic solution
- Easy to apply
- Gives a clear, colorless finish
- Treated timber complies with EN 13501-1 class C-s2, d0, M2 (France), British Standard 476 class 2 and many other relevant fire standards



No Fear No Fire!

**AD** Magma Industries

Markweg Zuid 27
4794 SN Heijningen
The Netherlands

E info@magma.nl
W www.magma.nl

TRADENAME	MAGMA FIRESTOP® TG-3												
DESCRIPTION	Waterborne, impregnating, fire retardant coating												
COLOR	White, colorless after drying												
LABOUR CLASSIFICATION	Complies with the Dutch labour standards for professional usage including VOC levels												
RECOMMENDED USE	As a fire retardant spray coating for treatment of timber												
FIRE CLASSIFICATION	Various materials treated with this products and comply with standards like: EN 13501-1 class C-s2, d0, NEN6065 cl.2 (Neth.), NF P 92-501 A2 (Belg.)/ M2 (Fr.), BS 476 part 7 cl. 2 (UK)												
COVERAGE	Depends on the quality and absorbing properties of the wood you like to treat. In general: 7-11 m ² per liter (6-10 m ² per Kg.)												
TECHNICAL DATA	<table> <tr> <td>Type</td> <td>: Fire retardant prime coating</td> </tr> <tr> <td>Basis</td> <td>: Vinyl/acrylic polymer</td> </tr> <tr> <td>Density</td> <td>: ± 1,13 kg/dm³</td> </tr> <tr> <td>PH value</td> <td>: ± 7,0</td> </tr> <tr> <td>VOC</td> <td>: 52,1 gr/ltr</td> </tr> </table>	Type	: Fire retardant prime coating	Basis	: Vinyl/acrylic polymer	Density	: ± 1,13 kg/dm ³	PH value	: ± 7,0	VOC	: 52,1 gr/ltr		
Type	: Fire retardant prime coating												
Basis	: Vinyl/acrylic polymer												
Density	: ± 1,13 kg/dm ³												
PH value	: ± 7,0												
VOC	: 52,1 gr/ltr												
APPLICATION	<table> <tr> <td>Dilution</td> <td>: Product is ready-to-use and cannot be diluted with other products and/or water, this will influence the FR quality.</td> </tr> <tr> <td>Method</td> <td>: Can be applied by spray, roller, immersion or industrial spray application</td> </tr> <tr> <td>Conditions</td> <td>: Temperature min. 5°C / max. 40°C. RH max. 70%.</td> </tr> <tr> <td>Surface</td> <td>: Remove any and all previous coatings, sealers, paints, stains, preservatives, etc. before applying this product. Surface needs to be clean, dry and free from dirt, dust or oil.</td> </tr> <tr> <td>Cleaning</td> <td>: Direct after treatment, with warm water before drying</td> </tr> <tr> <td>General</td> <td>: Before treatment, spray a small sample of the material, where it will not be noticed to ensure the result. When the result is not satisfactory, please do not work further with the product further and contact us.</td> </tr> </table>	Dilution	: Product is ready-to-use and cannot be diluted with other products and/or water, this will influence the FR quality.	Method	: Can be applied by spray, roller, immersion or industrial spray application	Conditions	: Temperature min. 5°C / max. 40°C. RH max. 70%.	Surface	: Remove any and all previous coatings, sealers, paints, stains, preservatives, etc. before applying this product. Surface needs to be clean, dry and free from dirt, dust or oil.	Cleaning	: Direct after treatment, with warm water before drying	General	: Before treatment, spray a small sample of the material, where it will not be noticed to ensure the result. When the result is not satisfactory, please do not work further with the product further and contact us.
Dilution	: Product is ready-to-use and cannot be diluted with other products and/or water, this will influence the FR quality.												
Method	: Can be applied by spray, roller, immersion or industrial spray application												
Conditions	: Temperature min. 5°C / max. 40°C. RH max. 70%.												
Surface	: Remove any and all previous coatings, sealers, paints, stains, preservatives, etc. before applying this product. Surface needs to be clean, dry and free from dirt, dust or oil.												
Cleaning	: Direct after treatment, with warm water before drying												
General	: Before treatment, spray a small sample of the material, where it will not be noticed to ensure the result. When the result is not satisfactory, please do not work further with the product further and contact us.												
PACKAGING	10 & 25 kg cans												
SHELF LIFE	Closed packing, 12 months, when packing has been opened the shelf life is limited to a period of 3-6 months												
TRANSPORT & STORAGE	Free from frost, not in direct sunlight, packaging well closed and keep away from children and animals												
SAFETY	For more information we direct you to our Material Safety Data Sheet												
GENERAL	It is important and recommended to take notice of general safety & hygiene precautions also for safe, waterborne chemicals. Do not eat, drink or smoke during application. Do not flush unused chemicals but dispose this in accordance with local waste disposal regulations												

All information in this document is correct on the day of issuing. We are allowed to change this information without notification. The fire classes as a.m. can only be reached by a professional application with right coverage rates. Liability based on this document can be dismissed